



K.1.IMP36N.FCT.0
imop 36

Includes standard medium brush, squeegee and rubber wheels.

Batteries



K.1.S.115.1163.357
i-power 14U

battery

K.1.S.115.0142.0

i-charge charger

Tanks



K.1.S.115.0089.0
Recovery tank

Replacement recovery water tank.



K.1.S.115.0079.0B
Clean water tank

Replacement clean water tank.



K.1.S.115.1079.2AT
Clean water tank with i-dose

Replacement clean water tank.

Brushes



K.2.S.115.1054.70
Brush Lite Soft

For light duty cleaning. Use on timber and delicate floors.



K.2.S.115.1054.797
Brush Lite Medium

For everyday scrubbing and cleaning.



K.2.S.115.1054.1
Brush Lite Hard

For use with deep cleaning including grout lines.



K.2.S.115.1054.592
Brush Lite Natural

For rubber floors, cork floors and timber sports halls.



K.2.S.115.1056.797
Pad driver Lite

Use in combination with all our pads.

Traditional pads (from least to most aggressive cleaning)



K.20.115.1057.2
White

Light buffing & polishing.



K.20.115.1057.1
Red

Regular buffing and cleaning pad.



K.20.115.1057.79
Blue

Heavy cleaning pad, dull or unsealed floors.



K.20.115.1057.64
Green

Aggressive scrubbing pad, unsealed floors.



K.20.115.1057.0
Black

Very aggressive scrubbing and stripping.

i-dose



K.120.72.0444.6
i-dose 7 Degrease
Green



K.120.72.0444.111
i-dose 3 Sanitary
Pink



K.120.72.0444.7
i-dose 5 Daily
Blue



K.120.72.0444.0
i-dose 3/5/7
Mixed



faster



cleaner



greener



safer



better

Squeegees



K.1.S.115.0062.357

Kit squeegee Linatex

Standard for imop
Lite.



K.1.S.115.0062.2

Kit squeegee Primothane

For imop Lite.

Rubbers



K.10.115.0065.2C

Lite FRONT Linatex



K.10.115.0066.2C

Lite REAR Linatex



K.10.115.0065.0

Lite FRONT Primothane



K.10.115.0066.0

Lite REAR Primothane

Linatex squeegee rubbers (standard)
High quality, durable and chemical
resistant.

Primothane squeegee rubbers
Specially designed for longer life in very oily
and greasy environments.

Technical specifications imop 36



Theoretical performance	1.400 m ² – based on i-power 14U (71 minutes runtime) 1260m ² /h
Practical performance	820 m ²
Brush speed	355 RPM
Brush pressure	Without water: 10.9kg With water: 14 kg (3.5 L) 0.26 kg/cm ²
Operation width	360 mm
Size machine (l x w x h)	430x270x1150mm
Weight without batteries & water	9.9 kg
Weight with batteries & water 3Ltr	14.9 kg
Clean water tank	3 L
Recovery tank	4 L
Noise level	Brush only: 58 dB/vac + brush: vac + brush 72 dB
Power source	i-power 14U, i-power 20U *
Battery spec	i-power 14U: 18.0 V (14 Ah)
Runtime	i-power 14U: 71 minutes
Charger type	100-240 V, 50/60 Hz
Charger	i-charge 5 *

* Batteries and charger can be ordered separately.

M25.000105.01.EN - Subject to change.

i-teamglobal.com