



COB45.SFT.1100C

SAFE-T-BOT 45

Includes 1 PC i-Power
20 + i-Charge single
battery

Brushes



K.1.S.130.0015.1

Kit assy brush roll

Hard
Red
Optional



K.1.S.130.0015.797

Kit assy brush roll

Soft
Darkblue
Optional



K.1.S.130.0015.70

Kit assy brush roll

Hard
Blue
Optional

Squeegees



K.10.130.0012.0

Kit squeegee

rubber rear

Primothane

Blue
Optional



K.10.130.0013.0

Kit squeegee

rubber rear

Primothane

Blue
Optional



K.10.130.0010.0

Kit squeegee

rubber front

Linatex

Red
Optional



K.10.130.0011.0

Kit squeegee

rubber front

Linatex

Red
Optional

Accessoires



K.1.S.300.0025.0

Kit assy i-charge

single 10A EU



S.72.2079.357

Assy i-power 20

right co-botic™ 45



K.1.S.72.1344.0

Kit assy i-charge 9

universal



K.1.72.0641.797

Kit exhaust filter

hepa

Blue



130.0154.0

Filter bag

co-botic™ 45



faster



cleaner



greener



safer



better

Technical specifications SAFE-T-BOT 45

Cleaning efficiency	Roller Scrubber/dryer upto 1500 m2 (Single Operation Cycle)
Cleaning pressure	2-6 kg
Clean water tank	10 L
Recovery tank	10 L
Battery life	2-3 hours (1 x ipower20)
Charging time	Single charger: 180mins i-charge 9c: 120 mins
Sensors	3D TOF (x2), 2D LiDAR (x1), Ultrasonic Sensors (x4)
Display screen	7 inches
Operational speed	0.8 m/s (adjustable)
Noise level	75 dB (power) / 71 dB (standard) / 65 dB (quiet)
Weight	35 kg
Dimensions (L x W x H)	500 mm X 504 mm X 629 mm
Brush speed	300-900 RPM
Other	Remote control, Auto route planner, Robot management dashboard, Downloadable cleaning reports (pdf file), Modular design on all parts
Voice language	English, Chinese, Korean
Visual interface	English, Chinese, German, Danish, Dutch, Finnish, Italian, Norwegian, Polish, Portuguese, Spanish, Swedish, French, Korean

