



COB45.I-V.1100C  
**Co botic™ 45 Ready EU**  
 Includes 1 PC i-Power  
 20 + i-Charge single  
 battery

## Brushes



K.1.S.130.0015.1  
**Kit assy brush roll**  
 Hard  
 Red  
 Optional



K.1.S.130.0015.797  
**Kit assy brush roll**  
 Soft  
 Darkblue  
 Optional



K.1.S.130.0015.70  
**Kit assy brush roll**  
 Hard  
 Blue  
 Optional

## Squeegees



K.10.130.0012.0  
**Kit squeegee rubber rear**  
**Primothane**  
 Blue  
 Optional



K.10.130.0013.0  
**Kit squeegee rubber rear**  
**Primothane**  
 Blue  
 Optional



K.10.130.0010.0  
**Kit squeegee rubber front**  
**Linatex**  
 Red  
 Optional



K.10.130.0011.0  
**Kit squeegee rubber front**  
**Linatex**  
 Red  
 Optional

## Accessoires



K.1.S.300.0025.0  
**Kit assy i-charge**  
**single 10A EU**



S.72.2079.357  
**Assy i-power 20**  
**right co-botic™ 45**



K.1.S.72.1344.0  
**Kit assy i-charge 9**  
**universal**



K.1.S.130.0147.0  
**Kit assy filter dirt**  
**tank co-botic™ 45**



130.0154.0  
**Filter bag**  
**co-botic™ 45**



faster



cleaner



greener



safer



better

## Technical specifications Co-botic™ 45

Cleaning efficiency	Roller Scrubber/dryer upto 1500 m2 (Single Operation Cycle)
Cleaning pressure	2-6 kg
Clean water tank	10 L
Recovery tank	10 L
Battery life	2-3 hours (1 x ipower20)
Charging time	Single charger: 180mins i-charge 9c: 120 mins
Sensors	3D TOF (x2), 2D LiDAR (x1), Ultrasonic Sensors (x4)
Display screen	7 inches
Operational speed	0.8 m/s (adjustable)
Noise level	75 dB (power) / 71 dB (standard) / 65 dB (quiet)
Weight	35 kg
Dimensions (L x W x H)	500 mm X 504 mm X 629 mm
Brush speed	300-900 RPM
Other	Remote control, Auto route planner, Robot management dashboard, Downloadable cleaning reports (pdf file), Modular design on all parts
Voice language	English, Chinese, Korean
Visual interface	English, Chinese, German, Danish, Dutch, Finnish, Italian, Norwegian, Polish, Portuguese, Spanish, Swedish, French, Korean

