



EMV.SFT.0000B
SAFE-T-VAC

Included in the box



S.55.0517.000
**2,5 Meter ESD
hose with handle**



55.1087.000
**Under floor hand
tool**



S.02.0032.6
Crevice tool



22.0034.41
**2x wand
stainless steel**



22.9045.610_32
Cleanroom nozzle

Accessories



55.0487.2
5 layers cloth bag



55.0453.0
Cloth filter cap



55.1099.701
**ULPA 15 round
filter**



55.1097.701
**ULPA 15 air-out
filter**



22.9045.720C
**Standard floor
nozzle**

Batteries



K1.S.119.0101.0
**i-charge 5S - 4X
ESD certified**



K1.S.119.0001.3
**i-power 8.7
Battery**



K1.S.119.0123.797
**i-power 10.5
Battery**



K1.S.119.0100.0
**i-Charger 5A-4X
with EU cable**



faster



cleaner



greener



safer



better

Technical specifications SAFE-T-VAC

Machine weight included 2x Batteries (ex. Hose and wand)	7.7 kg
2x batteries weight	0.70*2kg
Use battery model (two options available)	i-power 8.7 (14.4V, 8.7Ah) i-power10.5 (14.4V, 10.5Ah)
Dust bag capacity	>6.0L
Machine Size (W*T*H)	ø310X401MM
Battery duration(minutes)	43 minutes (i-power8.7, 2x) 52 minutes (i-power10.5, 2x)
Charger-time	105 minutes in i-charger 5A-4X (i-power8.7) 125 minutes in i-charger 5S-4X (i-power10.5)
Battery q'ty for 1x charger	4x for i-charger 5A-4X
Air flow rate (MAX) L/S	>33.65 L/S
Sealing suction	21-23 Kpa
Speed adjustment	NO
Current (Max)	10.6A
Rotary hose coupling	Yes
Machine motor type	DC28V, 300W, Brushless motor
Hose inside diameter	32mm
Noise level minimum (at L*H=1*1m)	65 dB
Filtration system	4-channel filtration system, ULPA –U15 Filter
Power switch (on/off)	Foot pression
Material of product	Stainless steel, steel, PP, ABS, Silicon rubber, aluminium, PP ESD...
2x wands and bend handle height	120 cm
Suction power test for sand in carpet (efficiency)	99%
Suction power test for flour in carpet (efficiency)	91%
Designed for cleanroom use	Passed ISO CLASS 5 Passed ISO CLASS 4



i-teamglobal.com

Headquarters • Eindhoven • Netherlands • +31 40 266 24 00 • hello@i-teamglobal.com