

imop Lite



IMOPLT.FCT.1100C imop Lite Includes standard medium brush, squeegee and rubber wheels.

Batteries



K.1.S.115.0143.0 i-power battery

K.1.S.115.0142.0 i-charge charger



S.115.0248.797 i-power 12 battery

K1.S.115.1389.2 i-charge charger



Tanks

K.1.S.115.0089.0 **Recovery tank** Replacement recovery water tank.



Clean tank Replacement clean water tank.



K.1.S.115.1079.2AT **Clean tank with** i-dose Replacement clean water tank.

Brushes



K.2.S.115.1054.70 **Brush Lite Soft** For light duty cleaning. Use on timber and delicate floors.



K.2.S.115.1054.797 **Brush Lite Medium** Standard supplied with i-mop.



K.2.S.115.1054.1 **Brush Lite Hard** For use with deep cleaning including grout lines.



K.2.S.115.1054.592 **Brush Lite Natural** timber sports halls.

Pad driver



K.2.S.115.1056.797 **Pad driver Lite** Use in combination with all our pads.

Twister pad



K.2.115.1060.64R Daily cleaning on stone, concrete, ceramic, vinyl, timber, rubber floors.



For everyday scrubbing and cleaning.





Regular pads (from least to most aggressive cleaning)



K.20.115.1057.2 White Light buffing & polishing.



Red Regular buffing and cleaning pad.



K.20.115.1057.79 Blue Heavy cleaning pad, dull or unsealed floors.



K.20.115.1057.64 Green Aggressive scrubbing pad, unsealed floors.



K.20.115.1057.0 Black Very aggressive scrubbing and stripping.

Cleaning



K.1.72.0324.0 **Cleaning brush** For imop dirt tank.



i-dose

K.120.72.0444.6 i-dose 7 Degrease Green



K.120.72.0444.111 i-dose 3 Sanitary Pink



K.120.72.0444.7 i-dose 5 Daily Blue



K.120.72.0444.0 i-dose 3/5/7 Mixed





Squeegees

Rubbers



K.1.S.115.0062.357 **Kit squeegee Linatex** Standard for imop Lite.

ARRAN

/ears

-

K.1.S.115.0062.2 **Kit squeegee Primothane** For imop Lite.

©



K.10.115.0065.2C Lite FRONT Linatex

resistant.

Linatex squeegee rubbers (standard)

High quality, durable and chemical

- Incide

K.10.115.0066.2C Lite REAR Linatex 2

K.10.115.0065.0

Lite FRONT

Primothane



K.10.115.0066.0 Lite REAR Primothane

Primothane squeegee rubbers

Specially designed for longer life in very oily and greasy environments.

Technical specifications imop Lite

Application	Indoor, hard surfaces only
Theoretical performance	1400 m ² per hour
Practical performance	700 - 1000 m² per hour
Brush speed	500 RPM
Brush pressure	13 kg
Operation width	37 cm
Size machine (I x w x h)	34 x 43 x 120 cm
Weight without battery & water	11.5 kg
Weight with batteries & water 3Ltr	16 kg
Clean water tank	3 Ltr
Recovery tank	3 to max 5 Ltr
Noise level	68 dB
Material	PP, Aluminum alloy
Power source	i-power 12*
Battery spec	i-power 12: 18 V, 12 Ah
Runtime	i-power 12: 45 minutes
Charger type	Off-board*
Charger	110-240 V, 50/60 Hz
Recovery tank Noise level Material Power source Battery spec Runtime Charger type	3 to max 5 Ltr 68 dB PP, Aluminum alloy i-power 12* i-power 12: 18 V, 12 Ah i-power 12: 45 minutes Off-board*

* Batteries and charger can be ordered separately.

i-teamglobal.com