



K.1.IMOPXLE.FCT.0
**SAFE-T-IMOP XL
PRO ISO 5/6
w/o i-power
*black***



K.1.IMOPXLE.FCT.1
**SAFE-T-IMOP XL
PRO ISO 7/8
w/o i-power
*black***

Charger and Batteries



K.1.S.72.1299.0
**Kit assy i-charge
EU**



K.1.S.72.4074.0
**Kit assy i-power
10 S
left**



K.1.S.72.4079.0
**Kit assy i-power
10 S
right**

Brushes



K.2.S.72.0092.8
**Kit assy brush XL
yellow**

Squeegees



K.1.S.72.0601.31/000
**Kit assy ez
squeegee XL
Primothane/FKM**



K.4.72.0238.8
**Kit squeegee
casters FKM
4 pieces**



faster



cleaner



greener



safer



better

Tanks



K.1.S.72.0081.5
**Kit assy clean tank
XL antimicrobial**



K.1.S.72.0088.5
**Kit assy dirt tank
XL antimicrobial**

Accessories



K.1.S.72.0670.0
**Kit assy enclosed
splash guard**



K.2.72.0029.8/0
**Kit transport
caster FKM**
2 pieces



K.1.72.0641.1
**Kit filter ULPA
U15 vacuum
motor**



K.1.72.0641.797
**Kit filter HEPA
H12 vacuum
motor**
*Not for use in Iso class
5/6 clean rooms.

Technical specifications SAFE-T-IMOP

Application	Indoor, hard surfaces only
Theoretical performance	Up to 1300 m ² per hour
Practical performance	400 - 800 m ² per hour
Brush speed	350 RPM
Brush pressure	22,5 kg
Operation width	46 cm
Size machine (l x w x h)	50 x 38 x 120 cm
Weight without batteries	18,5 kg
Clean water tank	4 L
Recovery clean tank	4-6 L (max. 8 L)
Material	PP, Aluminium alloy, stainless steel
Power source	2 i-power 10 S batteries
Battery	24V - 8.8 Ah
Run time	60 minutes on i-power 10 S batteries
Charger type	Off-board
Charger	110-240V, 50/60Hz
Charge time 10S batteries	4 h
Air pressure from out of the filter	2.03 m/s



i-teamglobal.com